

Sturm PG8735N

Tool series	Sturm
Maximum power, kW	3.5
Nominal power, kW	2.8
output voltage,	220
Number of phases	monophase
Engine type	OHV , gasoline , four-stroke
Engine model	LT168F-1
Engine volume, cubic see	196
Fuel type	gasoline AI-92
Fuel tank volume, l	15
The volume of oil in the crankcase, l	0.6
Maximum fuel consumption, l/h.	1.0
Starter type	manual
Number of sockets 230V	2
DC output 12V	1
Alternator winding material	copper
Automatic adjustment of AVR output voltage	yes
Automatic stop when the oil level is low	yes
Fuel level indicator	yes
Voltmeter	digital
Engine hours counter	yes
Connecting the autostart system	there is no
Noise level, dB	67
Weight, kg	43
Type of packaging	carton
Package dimensions, mm	-
Warranty period, months	24
Producing country	China
Brand registration country	Germany

START PRO SPG-3500 3.2 kW

The main ones	
Producer	Start Pro
Brand country	Ukraine
Fuel type	Gasoline
Generator type	Synchronous
Construction	Portable
Number of phases	1
High-voltage	220.0 (V)
Rated amperage	11.4 (A)
Current frequency	50 (Hz)
Capacity	3.0 (kW)
Maximum power	3.2 (kW)
Time of continuous operation	10.0 (time)
Degree of IP protection	23
Overload protection	Yes
Short circuit protection	Yes
Warranty period	12 (months)
State	New
Engine	
Engine capacity	196.0 (cubic cm)
Engine oil system volume	0.6 (l)
The volume of the fuel tank	12.0 (l)
Engine power	7.0 (hp)
Engine tact	Four stroke
Fuel consumption mini	0.395 (l/h)
Engine cooling system	Air
Overall dimensions	620*450*430 mm.
Weight	37.0 (kg)
Additional characteristics	
Launch modes	Manual start
Noise level	67.0 (dB)
Oil level sensor	Yes
Carrying handle	Yes

Gasoline generator Rolwal RB-J-GE3000X

Brand	Rolwal
Voltage, V	220
Frequency, Hz	50
Nominal output power, W	2800
Maximum output power, W	2500
Maximum power, hp	6.5
Nominal current, A	11.4
Engine type	170F, single cylinder, 4 stroke
Engine working volume, cm ³	196
The volume of the fuel tank l	12
The volume of oil in the crankcase, l	0.6
Fuel	gasoline
The average time of continuous operation of the generator, time	10-15
Noise level dB	67
Fuel consumption (min.), l/h	0.395
Engine cooling	aerial
Startup type	manual
Number of outlets, pcs.	2
Automatic Voltage Regulator (AVR)	Yes
Anti-vibration system	Yes
Overload and short circuit protection	Yes
Low oil protection	Yes
Voltmeter	Yes
Fuel level sensor	Yes
Ergonomic design	Yes
Weight: kg	37
Warranty month	12

Sturm PG8735EN	
Tool series	Sturm
Maximum power, kW	3.5
Nominal power, kW	2.8
output voltage,	220
Number of phases	monophase
Engine type	OHV , gasoline , four-stroke
Engine model	LT168F-1
Engine volume, cubic see	196
Fuel type	gasoline AI-92
Fuel tank volume, l	15
The volume of oil in the crankcase, l	0.6
Maximum fuel consumption, l/h.	1.0
Starter type	manual , electric
Number of sockets 230V	2
DC output 12V	1
Alternator winding material	copper
Automatic adjustment of AVR output voltage	yes
Automatic stop when the oil level is low	yes
Fuel level indicator	yes
Voltmeter	digital
Engine hours counter	yes
Connecting the autostart system	there is no
Noise level, dB	67
Weight, kg	43
Type of packaging	carton
Package dimensions, mm	-
Warranty period, months	24
Producing country	China
Brand registration country	Germany